

MAGNUM[®]

CUTTER/CREASER/PERFORATOR

Create professional results without the cost of outsourcing.

INTELLECTUAL PROPERTY

- Colour indexed slitter position

KEY FEATURES

- 3-in-1 systems to cut/crease or perforate
- Easy-to-use
- Accurate and time-saving
- Heavy duty

GREAT FOR USE IN

- Digital printers
- Copyshops
- Commercial printers
- Inplant print rooms

IDEAL WHEN CUTTING/CREASING

- Menus
- Book covers
- Leaflets
- Business cards
- Invitations

OPTIONAL TOOLS

- Cross perforation bar (6/8/12/24/52TPI)
- Creasing bars (0.4, 0.6, 1, 1.2, 1.4mm)



▲ MCC-35

Features

MCC-35

- Easily exchangeable slide-in crease/perforate tools
- High speed job changeover with preset programs
- Create up to 32 cut, crease or perforations in one pass
- Position adjustable slit heads
- Supports laminated stocks
- Hand feed with central register
- High volume waste bin
- Linear image shift

MCC-35A Includes all of the above plus :

- 230mm touch screen display and control
- Top vacuum feeding with central registration
- Ultrasonic double feed detector

Specifications

	MCC-35	MCC-35A
Infeed	Semi-Automatic	Automatic
Infeed Size	208x208xmm-330x650mm	208x208mm-330x650mm
Outfeed Size	50-48mm-330x650mm	50-48mm-330x650mm
Paper Weight	100-350gsm	100-350gsm
Paper Type	Chrome, Laminated, UV Coated, etc	Chrome, Laminated, UV Coated, etc
Accuracy	+/-0.2mm	+/-0.2mm
Crease Width	Interchangeable crease (0.4, 0.6, 1, 1.2, 1.4mm)	Interchangeable crease (0.4, 0.6, 1, 1.2, 1.4mm)
Crease/Perf in one Pass	Up to 32 times in one pass	Up to 32 times in one pass
Slitting	4 slitters	4 slitters
	2 side trimmer	2 side trimmer
	2 gutter slitter with fixed 8mm gap	2 gutter slitter with fixed 8mm gap
Speed	Up to 20 sheets/minute (SRA3/4 Trims)	Up to 20 sheets/minute (SRA3/4 Trims 1 Crease)
Image shrink and stretch	Feeding Direction	Feeding Direction
Gutter slit	8mm	8mm
Gutter cut	0 or 3-15mm	0 or 3-15mm
Feeding Type	Manual	50mm Vacuum pile feeder
Optional tools	Cross Perforator/ Creasing bars (0.4, 0.6, 1, 1.2, 1.4mm)	Cross Perforator/ Creasing bars (0.4, 0.6, 1, 1.2, 1.4mm)
Voltage	230V, 50Hz	230V, 50Hz
Overall dimensions (mm)	1280x580x1300	1680x580x1140
Gross weight	90kg	116kg

*For full terms & conditions on parts and labour warranty, visit vivid-online.com/support/warranty_information